



Category:Audio hardware components

Category:Audio hardware components



Contents

| | |
|---|---|
| 1. Category:Audio hardware components | 3 |
| 2. Audio codecs hardware components | 4 |



A quality version of this page, approved on *17 June 2020*, was based off this revision.

This category groups together all articles related to the **audio** hardware components used on the STM32 MPUs boards, and for which additional software information is needed.



Pages in category "Audio hardware components"

This category contains only the following page.

- [Audio codecs hardware components](#)

Stable: 02.06.2020 - 14:38 / Revision: 27.05.2020 - 15:56

A quality version of this page, approved on 2 June 2020, was based off this revision.

Contents

| | |
|-----------------------------|----|
| 1 Article purpose | 5 |
| 2 Software frameworks | 6 |
| 3 Wolfson wm8994 | 7 |
| 3.1 Linux driver | 7 |
| 4 Cirrus cs42l51 | 8 |
| 4.1 Linux driver | 8 |
| 5 Silab sil9022 | 9 |
| 5.1 Linux driver | 9 |
| 6 ST MP34DT01-M | 10 |
| 6.1 Linux driver | 10 |



1 Article purpose

The purpose of this article is to:

- list the audio codec hardware components that might be integrated in the different STM32MPU boards
- link these components to the corresponding software framework(s)
- point to the datasheet(s) of these components
- explain, when necessary, how to configure these components.



2 Software frameworks

| Domain | Peripheral | Software frameworks | | Comment |
|---------------------------------|------------------------------------|--------------------------|----------------|--------------------------|
| Cortex-A7 secure (OP-TEE) | Cortex-A7 non-secure (Linux) | Cortex-M4 (STM32Cube) | | |
| Audio | Wolfson wm8994 | | ALSA framework | DAC & ADC audio codec |
| Audio | Cirrus cs42l51 | | ALSA framework | DAC & ADC audio codec |
| Audio | Silab sil9022 | | ALSA framework | HDMI transmitter |
| Audio | ST MP34DT01- M | | ALSA framework | Digital microphone |



3 Wolfson wm8994

The WM8994 is a highly integrated ultra-low power hi-fi CODEC rich in multimedia features.

For details and the datasheet please contact the WM8994 codec provider.

3.1 Linux driver

Bindings: [Documentation/devicetree/bindings/sound/wm8994.txt](#)

Sources:

- [drivers/mfd/wm8994-core.c](#)
- [sound/soc/codecs/wm8994.c](#)
- [sound/soc/codecs/wm_hubs.c](#)



4 Cirrus cs42l51

The CS42L51 is a highly integrated, 24-bit, low-power stereo CODEC.

For details and the datasheet please contact the CS42L51 codec provider.

4.1 Linux driver

Bindings: [Documentation/devicetree/bindings/sound/cs42l51.txt](#)

Sources: [sound/soc/codecs/cs42l51.c](#)



5 Silab sil9022

The Sil9022A HDMI transmitter supports the HDMI[®] Specification on a wide range of mobile products.
For details and the datasheet please contact the Sil9022A HDMI transmitter provider.

5.1 Linux driver

Bindings: [Documentation/devicetree/bindings/display/bridge/sii902x.txt](#)

Sources: [drivers/gpu/drm/bridge/sii902x.c](#)



6 ST MP34DT01-M

The MP34DT01-M is an ultra-compact, low-power, omnidirectional, digital MEMS microphone.

Datasheet: <https://www.st.com/resource/en/datasheet/mp34dt01-m.pdf>

6.1 Linux driver

Bindings: `Documentation/devicetree/bindings/sound/dmic.txt`

Sources: `sound/soc/codecs/dmic.c`

Cortex[®]

Open Portable Trusted Execution Environment

Linux[®] is a registered trademark of Linus Torvalds.

Digital-to-analog converter (Electronic circuit that converts a binary number into a continuously varying value.)

Analog-to-digital converter. The process of converting a sampled analog signal to a digital code that represents the amplitude of the original signal sample.

High-Definition Multimedia Interface (HDMI standard)