

FMC device tree configuration

Stable: 16.09.2019 - 14:27 / Revision: 16.09.2019 - 14:26

Contents

| | |
|---|---|
| 1 Article purpose | 1 |
| 2 DT bindings documentation | 1 |
| 3 DT configuration | 1 |
| 3.1 DT configuration (STM32 level) | 1 |
| 3.2 DT configuration (board level) | 2 |
| 3.3 DT configuration examples | 2 |
| 4 How to configure the DT using STM32CubeMX | 3 |
| 5 References | 3 |

1 Article purpose

This article explains how to configure the **FMC internal peripheral** when it is assigned to the Linux[®] OS. In that case, it is controlled by the **MTD framework**.

The configuration is performed using the **device tree** mechanism that provides a hardware description of the FMC peripheral, used by the STM32 FMC Linux driver and by the MTD framework.

2 DT bindings documentation

The FMC device tree bindings are composed of:

- generic MTD nand bindings ^[1].
- FMC driver bindings ^[2].

3 DT configuration

This hardware description is a combination of the **STM32 microprocessor** device tree files (*.dtsi* extension) and **board** device tree files (*.dts* extension). See the **Device tree** for an explanation of the device tree file split.

STM32CubeMX can be used to generate the board device tree. Refer to **How to configure the DT using STM32CubeMX** for more details.

3.1 DT configuration (STM32 level)

The FMC peripheral node is located in *stm32mp157c.dtsi* ^[3] file.

```
fmc: nand-controller@58002000 {  
    compatible = "st,stm32mp15-fmc2";  
    reg = <0x58002000 0x1000>,  
        <0x80000000 0x1000>;
```

Comments

--> First region contains the
--> Régions 2 to 4 respective

```

        <0x88010000 0x1000>,
        <0x88020000 0x1000>,
        <0x81000000 0x1000>,
        <0x89010000 0x1000>,
        <0x89020000 0x1000>;
    interrupts = <GIC_SPI 48 IRQ_TYPE_LEVEL_HIGH>;
    dmas = <&mdma1 20 0x10 0x12000A02 0x0 0x0 0>,
        <&mdma1 20 0x10 0x12000A08 0x0 0x0 0>,
        <&mdma1 21 0x10 0x12000A0A 0x0 0x0 0>;
    dma-names = "tx", "rx", "ecc";
    clocks = <&rcc FMC_K>;
    resets = <&rcc FMC_R>;
    status = "disabled";
};

```

--> Régions 5 to 7 contain th

--> The interrupt number used

--> DMA specifiers ^[4]



This device tree part related to the STM32 should be kept as is, customer should not modify it.

3.2 DT configuration (board level)

The FMC peripheral may connect to one SLC NAND Flash memory (with a maximum of 2 dies per package).

```

&fmc {
    pinctrl-names = "default", "sleep";
    pinctrl-0 = <&fmc2_pins_a>;
    pinctrl-1 = <&fmc2_sleep_pins_a>;
    status = "okay";
    #address-cells = <1>;
    #size-cells = <0>;

    nand: nand@0 {
        reg = <0>;
        nand-on-flash-bbt;
        nand-ecc-strength = <8>;
        nand-ecc-step-size = <512>;
        #address-cells = <1>;
        #size-cells = <1>;
    };
};

```

Comments

--> For pinctrl configuration

--> Enable the node

--> Describe the CS line assi

--> Store the bad block table

--> Number of bits to correct

--> Number of data bytes that

The supported ECC strength and step size are:

- nand-ecc-strength = <1>, nand-ecc-step-size = <512> (HAMMING).
- nand-ecc-strength = <4>, nand-ecc-step-size = <512> (BCH4).
- nand-ecc-strength = <8>, nand-ecc-step-size = <512> (BCH8).

3.3 DT configuration examples

The below example shows how to configure the FMC controller when a SLC 8-bit NAND Flash memory device is connected (ECC requirement: 8 bits / 512 bytes).

```

&fmc {
    pinctrl-names = "default", "sleep";
    pinctrl-0 = <&fmc2_pins_a>;
    pinctrl-1 = <&fmc2_sleep_pins_a>;
    status = "okay";
    #address-cells = <1>;
};

```

```
#size-cells = <0>;

nand: nand@0 {
    reg = <0>;
    nand-on-flash-bbt;
    #address-cells = <1>;
    #size-cells = <1>;

    partition@0 {
        ...
    };
};
```

The below example shows how to configure the FMC controller when a SLC 8-bit NAND Flash memory device is connected (ECC requirement: 4 bits / 512 bytes).

```
&fmc {
    pinctrl-names = "default", "sleep";
    pinctrl-0 = <&fmc2_pins_a>;
    pinctrl-1 = <&fmc2_sleep_pins_a>;
    status = "okay";
    #address-cells = <1>;
    #size-cells = <0>;

    nand: nand@0 {
        reg = <0>;
        nand-on-flash-bbt;
        nand-ecc-strength = <4>;
        nand-ecc-step-size = <512>;
        #address-cells = <1>;
        #size-cells = <1>;

        partition@0 {
            ...
        };
    };
};
```

4 How to configure the DT using STM32CubeMX

The [STM32CubeMX](#) tool can be used to configure the STM32MPU device and get the corresponding [platform configuration device tree](#) files.

The STM32CubeMX may not support all the properties described in the above [DT bindings documentation](#) paragraph. If so, the tool inserts **user sections** in the generated device tree. These sections can then be edited to add some properties and they are preserved from one generation to another. Refer to [STM32CubeMX](#) user manual for further information.

5 References

Please refer to the following links for full description:

1. [↑ Documentation/devicetree/bindings/mtd/nand.txt](#)
2. [↑ Documentation/devicetree/bindings/mtd/stm32-fmc2-nand.txt](#)
3. [↑ arch/arm/boot/dts/stm32mp157c.dtsi](#)
4. [↑ Documentation/devicetree/bindings/dma/stm32-mdma.txt](#)

