



I2C internal peripheral



Contents

1. I2C internal peripheral	3
----------------------------------	---



Search for revisions From year (and earlier): From month (and earlier): Tag filter:

Diff selection: Mark the radio boxes of the revisions to compare and hit enter or the button at the bottom.

Legend: **(cur)** = difference with latest revision, **(prev)** = difference with preceding revision, **m** = minor edit.

- **(cur | prev)**09:38, 25 September 2020 **m** . . (5,546 bytes) (-1) [Reviewed: 09:43, 25 September 2020 |]
- **(cur | prev)**13:32, 3 February 2020 . . (5,547 bytes) (+2) . . (Add U-boot as runtime and removal of _ in the PMIC page link (related to boot time)) [Reviewed: 08:46, 21 February 2020 | | [Expert: Aproved, Technical writer: Approved, Maintainer: Approved]]
- **(cur | prev)**16:10, 18 January 2019 **m** . . (5,698 bytes) **(+5,698)** [Reviewed: 11:21, 11 February 2019 | | [Expert: Aproved, Technical writer: Approved, Maintainer: Approved]]

Stable: 25.09.2020 - 09:43 / Revision: 25.09.2020 - 09:38

Search for revisions From year (and earlier): From month (and earlier): Tag filter:

Diff selection: Mark the radio boxes of the revisions to compare and hit enter or the button at the bottom.

Legend: **(cur)** = difference with latest revision, **(prev)** = difference with preceding revision, **m** = minor edit.

- **(cur | prev)**09:38, 25 September 2020 **m** . . (5,546 bytes) (-1) [Reviewed: 09:43, 25 September 2020 |]
- **(cur | prev)**13:32, 3 February 2020 . . (5,547 bytes) (+2) . . (Add U-boot as runtime and removal of _ in the PMIC page link (related to boot time)) [Reviewed: 08:46, 21 February 2020 | | [Expert: Aproved, Technical writer: Approved, Maintainer: Approved]]
- **(cur | prev)**16:10, 18 January 2019 **m** . . (5,698 bytes) **(+5,698)** [Reviewed: 11:21, 11 February 2019 | | [Expert: Aproved, Technical writer: Approved, Maintainer: Approved]]