



# STM32CubeMP1 Package release note - v1.0.0



# STM32CubeMP1 Package release note - v1.0.0

Stable: 04.02.2020 - 08:03 / Revision: 04.02.2020 - 07:57

## Contents

1 Release information .....	2
2 Delivery scope and purpose .....	2
3 Supported devices .....	3
4 Supported hardware .....	3
5 Known issues and limitations .....	3
6 Contents .....	4
<b>6.1 Released projects .....</b>	<b>4</b>
<b>6.2 Released components .....</b>	<b>4</b>
<b>6.3 Available drivers .....</b>	<b>5</b>
6.3.1 HAL drivers .....	5
6.3.2 LL drivers .....	15
<b>6.4 Available projects .....</b>	<b>17</b>
7 Minor release updates .....	24
<b>7.1 STM32CubeMP1 Package v1.0.1 .....</b>	<b>25</b>
8 How to get started with STM32CubeMP1 Package .....	25
9 Associated tools .....	25
10 References .....	25

## 1 Release information

This article aims to describe the content of the **software** release included in the STM32CubeMP1 Package, version **v1.0.0**

## 2 Delivery scope and purpose

The **STM32CubeMP1 Package** is a software package running on **Arm® Cortex® M4** processors and is a fundamental part of the STM32MPU Embedded Software distribution.

This release includes:

- The STM32Cube HAL, STM32 abstraction layer embedded software ensuring maximized portability across the STM32 portfolio. HAL APIs are available for all peripherals.
- Low-layer APIs (LL) offering a fast lightweight expert-oriented layer that is closer to the hardware than the HAL. LL APIs are available only for a set of peripherals.
- A consistent set of middleware components such as FreeRTOS, OpenAMP.
- All embedded software utilities, delivered with a full set of examples.



It also includes:

- BSP for the STM32MP157C-EV1 Evaluation board and the STM32MP157C-DK2 Discovery kit (button and LEDs only)
- Multi-core components
  - OpenAMP
  - ResourceManager
  - CoproSync
- IDE ready projects (examples, applications and demonstration firmware) with the **System Workbench for STM32** toolchain (SW4STM32)

## 3 Supported devices

---

The drivers provided within this package support the following devices :

- STM32MP157Cxx, STM32MP157Axx
- STM32MP153Cxx, STM32MP153Axx
- STM32MP151Cxx, STM32MP151Axx

## 4 Supported hardware

---

This software delivery is applicable to the following boards:

- STM32MP157C-EV1 Evaluation board (RevC). For information about this board, read the article [STM32MP157C-EV1 - hardware description](#).
- STM32MP157C-DK2 Discovery board (RevC). For information about this board, read the article [STM32MP157X-DKX - hardware description](#).

## 5 Known issues and limitations

---

- CRYP1 and CRYP2 not declared in stm32MP153cxx\_cm4.h and stm32MP151cxx\_cm4.h files - see patch upper V1.0.0 in github [1]
- Some compilation issues in resmgr.c with STM32MP151xxx, STM32MP153xxx - see patch upper V1.0.0 in github [2]
- ADC warning in stm32mp1xx\_hal\_adc\_ex.h - see patch upper V1.0.0 in github [3]

## 6 Contents



**Note:**

- For detailed information, read file **Release\_Notes.html** delivered with the **STM32CubeMP1** package software.

### 6.1 Released projects

The **STM32CubeMP1 Firmware Package** comes with a rich set of examples running on **STMicroelectronics** boards, organized by board and provided with preconfigured projects for the main supported toolchain (**System Workbench for STM32**). The exhaustive list of projects is provided in the table [List of Projects](#).

- IDE ready projects

Projects	STM32MP157C-DK2	STM32MP157C-EV1
Availables Firmware	24	25

### 6.2 Released components

- Drivers

Component	Version	Notes
Cortex-M CMSIS V5.2.0	V5.2.0	
STM32MP1xx CMSIS	V1.0.0	
STM32MP1xx HAL	V1.0.0	
BSP STM32MP15xx_EVAL	V1.0.0	
BSP STM32MP15xx_DISCO	V1.0.0	

- Middleware

Component	Version	Notes
FreeRTOS	V10.0.1 ST modified 20180813	
OpenAMP	v2018.10 ST modified 20190125	

- Utilities



Component	Version	Notes
Resource manager	V1.5.0	

## 6.3 Available drivers

Please find below the list of HAL and LL drivers available:

### 6.3.1 HAL drivers

STM32CubeMP1 HAL Driver items	Description
ADC	<pre> *          This driver provides firmware functions to manage the following *          functionalities of the Analog to Digital Convertor (ADC) *          peripheral: *          + Initialization and de-initialization functions *          ++ Initialization and Configuration of AD C *          + Operation functions *          ++ Start, stop, get result of conversions of regular *          group, using 3 possible modes: polling, interruption or DMA. *          + Control functions *          ++ Channels configuration on regular group *          ++ Analog Watchdog configuration *          + State functions *          ++ ADC state machine management *          ++ Interrupts and flags management *          + Operation functions *          ++ Start, stop, get result of conversions of ADC group injected, *          using 2 possible modes: polling, interruption. *          ++ Calibration *          +++ ADC automatic self-calibration *          +++ Calibration factors get or set *          ++ Multimode feature when available *          + Control functions *          ++ Channels configuration on ADC group injected *          + State functions *          ++ ADC group injected contexts queue management </pre>



STM32CubeMP1 HAL Driver items	Description
CEC	<p>* This driver provides firmware functions to manage the following functionalities of the High Definition Multimedia Interface Consumer Electronics Control Peripheral (CEC).</p> <ul style="list-style-type: none"> <li>* + Initialization and de-initialization function</li> <li>* + IO operation function</li> <li>* + Peripheral Control function</li> </ul>
CRC	<p>* This driver provides firmware functions to manage the following functionalities of the Cyclic Redundancy Check (CRC) peripheral:</p> <ul style="list-style-type: none"> <li>* + Initialization and de-initialization functions</li> <li>* + Peripheral Control functions</li> <li>* + Peripheral State functions</li> <li>* + Extended features functions</li> </ul>
CORTEX	<p>* This driver provides firmware functions to manage the following functionalities of the CORTEX (MPU, Cache, ...):</p> <ul style="list-style-type: none"> <li>* + Initialization and de-initialization functions</li> <li>* + Peripheral Control functions</li> </ul>
CRYP	<p>* This driver provides firmware functions to manage the following functionalities of the Cryptography (CRYP) peripheral:</p> <ul style="list-style-type: none"> <li>* + Initialization and de-initialization functions</li> <li>* + AES processing functions</li> <li>* + DES processing functions</li> <li>* + TDES processing functions</li> <li>* + DMA callback functions</li> <li>* + CRYP IRQ handler management</li> <li>* + Peripheral State functions</li> <li>* + Extended AES processing functions</li> </ul>



L Driver items	
DAC	<p>* This driver provides firmware functions to manage the following</p> <ul style="list-style-type: none"><li>* functionalities of the Digital to Analog Converter (DAC) peripheral:</li><li>* + Initialization and de-initialization functions</li><li>* + IO operation functions</li><li>* + Peripheral Control functions</li><li>* + Peripheral State and Errors functions</li><li>* + Extended features functions</li></ul>
DCMI	<p>* This driver provides firmware functions to manage the following</p> <ul style="list-style-type: none"><li>* functionalities of the Digital Camera Interface (DCMI) peripheral:</li><li>* + Initialization and de-initialization functions</li><li>* + IO operation functions</li><li>* + Peripheral Control functions</li><li>* + Peripheral State and Error functions</li></ul>
DFSDM	<p>* This driver provides firmware functions to manage the following</p> <ul style="list-style-type: none"><li>* functionalities of the Digital Filter for Sigma-Delta Modulators (DFSDM) peripherals:</li><li>* + Initialization and configuration of channels and filters</li><li>* + Regular channels configuration</li><li>* + Injected channels configuration</li><li>* + Regular/Injected Channels DMA Configuration</li><li>* + Interrupts and flags management</li><li>* + Analog watchdog feature</li><li>* + Short-circuit detector feature</li><li>* + Extremes detector feature</li><li>* + Clock absence detector feature</li><li>* + Break generation on analog watchdog or short-circuit event</li><li>* + Set and get pulses skipping on channel.</li></ul>



STM32CubeMP1 HAL Driver items	Description
DMA	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the Direct Memory Access (DMA) peripheral:</p> <p>* + Initialization and de-initialization functions</p> <p>* + IO operation functions</p> <p>* + Peripheral State and errors functions</p> <p>* + Extended features functions</p>
EXTI	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the General Purpose Input /Output (EXTI) peripheral:</p> <p>* + Initialization and de-initialization functions</p> <p>* + IO operation functions</p>
FDCAN	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the Flexible DataRate Controller Area Network (FDCAN) peripheral:</p> <p>* + Initialization and de-initialization functions</p> <p>* + IO operation functions</p> <p>* + Peripheral Configuration and Control functions</p> <p>* + Peripheral State and Error functions</p>
GPIO	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the General Purpose Input /Output (GPIO) peripheral:</p> <p>* + Initialization and de-initialization functions</p> <p>* + IO operation functions</p> <p>* + Extended Peripheral Control functions</p>





STM32CubeMP1 HAL Driver items	Description
HAL	<p>* This driver provides firmware functions to manage the following functionalities of HAL, Tick, SYSCFG, DBGMCU:</p> <ul style="list-style-type: none"> <li>* + Initialization and de-initialization functions</li> <li>* + HAL Initialization and de-initialization functions</li> <li>* + Configure the source of the time base</li> <li>* + HAL Control functions</li> <li>* + Tick management (get/set/inc/priority/suspend/resume)</li> <li>* + Get HAL revision, the device revision identifier, the device identifier</li> <li>* + Enable/Disable DBG wake up on AIEC</li> <li>* + Enable/Disable the Debug Module during Domain1 SLEEP mode</li> <li>* + Enable/Disable the Debug Module during Domain1 STOP mode</li> <li>* + Enable/Disable the Debug Module during Domain1 STANDBY mode</li> <li>* + Configure the internal voltage reference buffer voltage scale</li> <li>* + Configure the internal voltage reference buffer high impedance mode</li> <li>* + Tune the Internal Voltage Reference buffer (VREFBUF)</li> <li>* + Enable/Disable the Internal Voltage Reference buffer (VREFBUF)</li> <li>* + Ethernet PHY Interface Selection either MII or RMII</li> <li>* + Analog Switch control for dual analog pads</li> <li>* + Enable/Disable the booster to reduce the total harmonic distortion of the analog</li> <li>* + Enable/Power-down the I/O Compensation Cell</li> <li>* + To Enable/Disable optimize the I/O speed when the product voltage is low</li> <li>* + Code selection for the I/O Compensation cell</li> </ul>
	<p>* This driver provides firmware functions to manage the following functionalities of the HASH peripheral:</p> <ul style="list-style-type: none"> <li>* + Initialization and de-initialization methods</li> <li>* + HASH or HMAC processing in polling mode</li> <li>* + HASH or HMAC processing in interrupt mode</li> </ul>



STM32CubeMP1 HAL Driver items	Description
HASH	<ul style="list-style-type: none"> <li>* + HASH or HMAC processing in DMA mode</li> <li>* + Peripheral State methods</li> <li>* + HASH or HMAC processing suspension /resumption</li> <li>* Additionally, this driver provides functions to manage HMAC</li> <li>* multi-buffer DMA-based processing for MD-5, SHA-1, SHA-224</li> <li>* and SHA-256.</li> </ul>
HSEM	<ul style="list-style-type: none"> <li>* This driver provides firmware functions to manage the following</li> <li>* functionalities of the semaphore peripheral:</li> <li>* + Semaphore Take function (2-Step Procedure) , non blocking</li> <li>* + Semaphore FastTake function (1-Step Procedure) , non blocking</li> <li>* + Semaphore Status check</li> <li>* + Semaphore Clear Key Set and Get</li> <li>* + Release and release all functions</li> <li>* + Semaphore notification enabling and disabling and callnack functions</li> <li>* + IRQ handler management</li> </ul>
I2C	<ul style="list-style-type: none"> <li>* This driver provides firmware functions to manage the following</li> <li>* functionalities of the Inter Integrated Circuit (I2C) peripheral:</li> <li>* + Initialization and de-initialization functions</li> <li>* + IO operation functions</li> <li>* + Peripheral State and Errors functions</li> <li>* + Extended features functions</li> </ul>
IPCC	<ul style="list-style-type: none"> <li>* This driver provides firmware functions to manage the following</li> <li>* functionalities of the Inter-Processor communication controller peripherals (IPCC).</li> <li>* + Initialization and de-initialization functions</li> <li>* + Configuration, notification and interrupts handling</li> <li>* + Peripheral State and Error functions</li> </ul>



L Driver items	
LPTIM	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the Low Power Timer (LPTIM) peripheral:</p> <ul style="list-style-type: none"><li>* + Initialization and de-initialization functions.</li><li>* + Start/Stop operation functions in polling mode.</li><li>* + Start/Stop operation functions in interrupt mode.</li><li>* + Reading operation functions.</li><li>* + Peripheral State functions.</li></ul>
MDIOS	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the MDIOS Peripheral.</p> <ul style="list-style-type: none"><li>* + Initialization and de-initialization functions</li><li>* + IO operation functions</li><li>* + Peripheral Control functions</li></ul>
MDMA	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the Master Direct Memory Access (MDMA) peripheral:</p> <ul style="list-style-type: none"><li>* + Initialization/de-initialization functions</li><li>* + I/O operation functions</li><li>* + Peripheral State and errors functions</li></ul>
PWR	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the Power Controller (PWR) peripheral:</p> <ul style="list-style-type: none"><li>* + Initialization and de-initialization functions</li><li>* + Peripheral Control functions</li><li>* + Peripheral Extended features functions</li></ul>



STM32CubeMP1 HAL Driver items	Description
QUADSPI	<p>* This driver provides firmware functions to manage the following functionalities of the QuadSPI interface (QSPI).</p> <p>* functions</p> <ul style="list-style-type: none"> <li>+ Initialization and de-initialization</li> <li>+ Indirect functional mode management</li> <li>+ Memory-mapped functional mode management</li> <li>+ Auto-polling functional mode management</li> <li>+ Interrupts and flags management</li> <li>+ MDMA channel configuration for indirect functional mode</li> <li>+ Errors management and abort functionality</li> </ul>
RCC	<p>* This driver provides firmware functions to manage the following functionalities of the Reset and Clock Control (RCC) peripheral:</p> <p>* functions</p> <ul style="list-style-type: none"> <li>+ Initialization and de-initialization</li> <li>+ Peripheral Control functions</li> <li>+ Extended Peripheral Control functions</li> </ul>
RNG	<p>* This driver provides firmware functions to manage the following functionalities of the Random Number Generator (RNG) peripheral:</p> <p>* functions</p> <ul style="list-style-type: none"> <li>+ Initialization and configuration</li> <li>+ Peripheral Control functions</li> <li>+ Peripheral State functions</li> </ul>
SAI	<p>* This driver provides firmware functions to manage the following functionalities of the Serial Audio Interface (SAI) peripheral:</p> <p>* functions</p> <ul style="list-style-type: none"> <li>+ Initialization/de-initialization</li> <li>+ I/O operation functions</li> <li>+ Peripheral Control functions</li> <li>+ Peripheral State functions</li> <li>+ Modify PDM microphone delays.</li> </ul>



L Driver items	
SD	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the Secure Digital (SD) peripheral:</p> <p>* functions</p> <ul style="list-style-type: none"><li>+ Initialization and de-initialization</li><li>+ IO operation functions</li><li>+ Peripheral Control functions</li><li>+ Peripheral State functions</li><li>+ Extended features functions</li></ul>
SMBUS	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the System Management Bus (SMBus) peripheral,</p> <p>* based on I2C principles of operation :</p> <p>* functions</p> <ul style="list-style-type: none"><li>+ Initialization and de-initialization</li><li>+ IO operation functions</li><li>+ Peripheral State and Errors functions</li></ul>
SPDIFRX	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the SPDIFRX audio interface:</p> <ul style="list-style-type: none"><li>+ Initialization and Configuration</li><li>+ Data transfers functions</li><li>+ DMA transfers management</li><li>+ Interrupts and flags management</li></ul>
SPI	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the Serial Peripheral Interface (SPI) peripheral:</p> <p>* functions</p> <ul style="list-style-type: none"><li>+ Initialization and de-initialization</li><li>+ IO operation functions</li><li>+ Peripheral Control functions</li><li>+ Peripheral State functions</li><li>+ IO operation functions</li><li>+ Peripheral Control functions</li></ul>



STM32CubeMP1 HAL Driver items	Description
TIMER	<pre> *          This driver provides firmware functions to manage the following *          functionalities of the Timer (TIM) peripheral: *          + Time Base Initialization *          + Time Base Start *          + Time Base Start Interruption *          + Time Base Start DMA *          + Time Output Compare/PWM Initialization *          + Time Output Compare/PWM Channel Configuration *          + Time Output Compare/PWM Start *          + Time Output Compare/PWM Start Interruption *          + Time Output Compare/PWM Start DMA *          + Time Input Capture Initialization *          + Time Input Capture Channel Configuration *          + Time Input Capture Start *          + Time Input Capture Start Interruption *          + Time Input Capture Start DMA *          + Time One Pulse Initialization *          + Time One Pulse Channel Configuration *          + Time One Pulse Start *          + Time Encoder Interface Initialization *          + Time Encoder Interface Start *          + Time Encoder Interface Start Interruption *          + Time Encoder Interface Start DMA *          + Commutation Event configuration with Interruption and DMA *          + Time OCREf clear configuration *          + Time External Clock configuration *          + Time Hall Sensor Interface Initialization *          + Time Hall Sensor Interface Start *          + Time Complementary signal bread and dead time configuration *          + Time Master and Slave synchronization configuration *          + Time Output Compare/PWM Channel Configuration (for channels 5 and 6) *          + Time OCREf clear configuration *          + Timer remapping capabilities configuration </pre>
	<pre> *          This driver provides firmware functions to manage the following *          functionalities of the Universal (Synchronous) Asynchronous Receiver Transmitter *          Peripheral (U(S)ART). *          + Initialization and de-initialization </pre>



STM32CubeMP1 HAL Driver items	Description
U(S)ART	<ul style="list-style-type: none"> <li>functions</li> <li>* + IO operation functions</li> <li>* + Peripheral Control functions</li> <li>* + Peripheral State and Error functions</li> <li>* + Peripheral Control functions</li> </ul>
WWDG	<ul style="list-style-type: none"> <li>* This driver provides firmware functions to manage the following</li> <li>* functionalities of the Window Watchdog (WWDG) peripheral:</li> <li>* + Initialization and Configuration functions</li> <li>* + IO operation functions</li> </ul>

### 6.3.2 LL drivers

STM32CubeMP1 LL Driver items	Description
ADC	<ul style="list-style-type: none"> <li>* This driver provides firmware functions to manage the following</li> <li>* functionalities of the ADC peripheral:</li> <li>* + Initialization/de-initialization functions</li> <li>* + Configuration functions (ADC instance, group regular, group injected, channels, analog watchdog, oversampling, multimode)</li> <li>* + IT/FLAGS management functions</li> </ul>
BUS	<ul style="list-style-type: none"> <li>* This driver provides firmware functions to manage the following</li> <li>* functionalities of the BUS peripheral:</li> <li>* + Enable/disable/reset clocks for all system BUS (AHB2, AHB3, AHB4, AHB5, AHB6, AXI, MLAHB, APB1, APB2, APB3, APB4, APB5)</li> </ul>



STM32CubeMP1 LL Driver items	Description
GPIO	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the GPIO peripheral:</p> <p>* + Initialization/de-initialization functions</p> <p>* + Data access functions</p> <p>* + Port configuration functions</p>
IPCC	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the IPCC peripheral:</p> <p>* + IT/FLAGS management functions</p> <p>* + Enable/disable transmit and receive channels functions</p>
RCC	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the RCC peripheral:</p> <p>* + Clocks management functions (HSE/HSI/CSI/LSE/LSI/MCO/PLL)</p> <p>* + RTC/TIMERS functions</p> <p>* + IT/FLAGS management functions</p> <p>* + De-initialization functions</p> <p>* + Get system and peripherals clocks frequency functions</p>
SYSTEM	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the SYSTEM peripheral:</p> <p>* + SYSCFG and DBGMCU functions</p>
	<p>* This driver provides firmware functions to manage the following</p> <p>* functionalities of the USART peripheral:</p> <p>* + Initialization/de-initialization functions</p> <p>* + Configuration functions (Irda, Smartcard, Half duplex,</p> <p>* SPI Slave, LIN, Driver enable)</p>



STM32CubeMP1 LL Driver items	Description
USART	<ul style="list-style-type: none"> <li>* + Advanced configurations services</li> <li>functions</li> <li>* + IT/FLAGS management functions</li> <li>* + DMA management functions</li> <li>* + Data management functions</li> <li>* + Execution functions</li> </ul>
UTILS	<ul style="list-style-type: none"> <li>* This driver provides firmware functions to manage the following</li> <li>* functionalities of the UTILS peripheral:</li> <li>* + Device Electronic Signature functions</li> <li>* + DELAY functions</li> <li>* + SYSTEM functions</li> </ul>

## 6.4 Available projects

Please find below the list of projects available for STM32MP157C-EV1 and STM32MP157C-DK2 :

	<p><b>Note:</b></p>	<ul style="list-style-type: none"> <li>Please refer to article <a href="#">Introduction to boot mode</a> to get more information about <b>Production</b> and <b>Engineering</b> modes</li> </ul>
--	---------------------	--

Level	Module Name	Project Name	Description	ST M32 MP1 57C - DK2	ST M32 MP1 57C - EV1	Mode	Core
Examples	ADC	ADC_SingleConversion_TriggerTimer_DMA	Use ADC to convert a single channel at each trig from timer, conversion data are transferred by DMA into an array, indefinitely (circular mode).	x	x	Production & Engineering	Core-M4
							C



Level	Module Name	Project Name	Description	ST M32 MP1 57C - DK2	ST M32 MP1 57C - EV1	Mode	Core
Examples	CRC	CRC_Us erDefine dPolyno mial	How to configure the CRC using the HAL API. The CRC (cyclic redundancy check) calculation unit computes the 8-bit CRC code for a given buffer of 32-bit data words, based on a user-defined generating polynomial.	x	x	Productio n & Engineeri ng	o r t e x - M 4
	CRYP	CRYP_A ES_DM A	This example provides a short description of how to use the CRYPTO peripheral to encrypt and decrypt data using AES-128 Algorithm with ECB chaining mode.	x	x	Productio n & Engineeri ng	C o r t e x - M 4
	CORT EX	CORTE XM_MP U	Presentation of the MPU feature. This example configures a memory area as privileged read-only, and attempts to perform read and write operations in different modes.	x	x	Productio n & Engineeri ng	C o r t e x - M 4
	DAC	DAC_Si mpleCon version	How to use the DAC peripheral to do a simple conversion.	-	x	Productio n & Engineeri ng	C o r t e x - M 4
	DMA	DMA_FI FOMode	This example provides a description of how to use a DMA to transfer a word data buffer from Fla sh memory to embedded SRAM with FIFO mode enabled through the HAL API.	x	x	Productio n & Engineeri ng	C o r t e x - M 4



Level	Module Name	Project Name	Description	ST M32 MP1 57C - DK2	ST M32 MP1 57C - EV1	Mode	Core
Examples							
	FDCA N	FDCAN_ Loopbac k	How to configure the FDCAN to operate in loopback mode.	x	x	Engineeri ng Only	C o r t e x - M 4
	GPIO	GPIO_E XTI	How to configure external interrupt lines.	x	x	Productio n & Engineeri ng	C o r t e x - M 4
	HASH	HASH_S HA224S HA256_ DMA	This example provides a short description of how to use the HASH peripheral to hash data using SHA224 and SHA256 Algorithms.	x	x	Productio n & Engineeri ng	C o r t e x - M 4
	I2C	I2C_Two Boards_ ComDM A	How to handle I2C data buffer transmission /reception between two boards, via DMA.	-	x	Productio n & Engineeri ng	C o r t e x - M 4
							C o r t e x - M



Level	Module Name	Project Name	Description	ST M32 MP1 57C - DK2	ST M32 MP1 57C - EV1	Mode	Core
Examples		I2C_Two Boards_ ComIT	How to handle I2C data buffer transmission /reception between two boards, using an interrupt.	x	x	Production & Engineering	4
	LPTIM	LPTIM_PulseCounter	This example describes how to configure and use LPTIM to count pulses through the LPTIM HAL API.	x	x	Production (DK2) & Engineering (EV1 and DK2)	Core x-M 4
	QSPI	QSPI_ReadWrite_IT	This example describes how to erase part of the QSPI memory, write data in IT mode, read data in IT mode and compare the result in a forever loop.	-	x	Production & Engineering	Core x-M 4
	SPI	SPI_Full Duplex_ ComDMA_Master	Data buffer transmission/reception between two boards via SPI in Polling.	x	x	Production & Engineering	Core x-M 4
		SPI_Full Duplex_ ComDMA_Slave	Data buffer transmission/reception between two boards via SPI using DMA.	x	x	Production & Engineering	Core x-M 4
							Co



Level	Module Name	Project Name	Description	ST M32 MP1 57C - DK2	ST M32 MP1 57C - EV1	Mode	Core
Examples		SPI_Full Duplex_ComIT_Master	Data buffer transmission/reception between two boards via SPI using Interrupt mode.	x	-	Production & Engineering	rtex-M4
		SPI_Full Duplex_ComIT_Slave	Data buffer transmission/reception between two boards via SPI using Interrupt mode.	x	-	Production & Engineering	Cortex-M4
	TIM	TIM_DMAburst	This example shows how to update the TIMER TIM2_CH4 period and the duty cycle using the TIMER DMA burst feature.	x	x	Production & Engineering	Cortex-M4
	UART	UART_TwoBoards_ComDMA	UART transmission (transmit/receive) in DMA mode between two boards.	x	-	Production & Engineering	Cortex-M4
		UART_TwoBoards_ComIT	UART transmission (transmit/receive) in Interrupt mode between two boards.	x	x	Production & Engineering	Cortex-M4
							C



Level	Module Name	Project Name	Description	ST M32 MP1 57C - DK2	ST M32 MP1 57C - EV1	Mode	Core
Examples	WWDG	WWDG_Example	Configuration of the HAL API to periodically update the WWDG counter and simulate a software fault that generates an MCU WWDG reset when a predefined time period has elapsed.	x	x	Production & Engineering	Cortex-M4
Applications	Total number of examples: 36			18	18		
	Copro Sync	CoproSync_Shut Down	Send of shutdown information to Cortex-M4 so that it is able to take necessary actions before going to reset state.	-	x	Production	Cortex-M4
	FreeRTOS	FreeRTOS_ThreadCreation	How to implement thread creation using CMSIS R TOS API.	x	x	Production & Engineering	Cortex-M4
							Cortex-M



Level	Module Name	Project Name	Description	ST M32 MP1 57C - DK2	ST M32 MP1 57C - EV1	Mode	Core
<b>Exam ples</b>							
	Open AMP	OpenAMP_TTY_echo	How to use OpenAMP MW + Virtual UART to create an Inter-Processor Communication channel seen as TTY device in Linux OS	x	x	Production	4
		OpenAMP_TTY_echo_wakeup	How to use OpenAMP MW to enter in different power system operating mode (Run, Stop and Standby).	x	x	Production	C o r t e x - M 4
		OpenAMP_raw	How to use OpenAMP MW to create an Inter-Processor Communication channel	x	x	Production	C o r t e x - M 4
<b>Demo nstrati ons</b>	Total number of applications: 9			4	5		
	AI	AI_Character_Recognition	This project demonstrate a complex application that is running on both CPU1(CA7) and CPU2 (CM4)	x	x	Production	C o r t e x - M 4
	Total						



Level	Module Name	Project Name	Description	ST M32 MP1 57C - DK2	ST M32 MP1 57C - EV1	Mode	Core
Examples							
Templates	number of demonstrations: 2			1	1		
	-	Starter project	This projects provides a reference template that can be used to build any firmware application in mode on Cortex-M4	x	x	Engineering	Cortex-M4
Total number of projects: 49	Total number of templates: 2			1	1		
				24	25		

## 7 Minor release updates

STMicroelectronics regularly delivers corrections through github<sup>®</sup> components. You can decide to incorporate them into your developer package or distribution package.

- Please refer to STM32MP1 Developer Package or How to switch to github<sup>®</sup> mode in distribution package.





---

## 7.1 STM32CubeMP1 Package v1.0.1

STM32CubeMP1 updates github release 1.0.1

# 8 How to get started with STM32CubeMP1 Package

---

- Please refer to [How to get software and start with this release](#)

## 9 Associated tools

---

- Please refer to [Referenced tools release notes](#) to obtain more information on all available tools.

## 10 References

---

Hardware Abstraction Layer

Low layer of STM32Cube

Board support package

(Software)Integrated development/design/debugging environment

Analog-to-digital converter. The process of converting a sampled analog signal to a digital code that represents the amplitude of the original signal sample.

Cortex Microcontroller Software Interface Standard

Evaluation board

Discovery kit

Direct Memory Access

Consumer Electronics Control (HDMI standard)

input/output

Cyclic redundancy check calculation unit

Microprocessor Unit

Cryptographic processor

Advanced Encryption Standard

Data Encryption Standard



Triple Data Encryption Standard

Digital-to-analog converter (Electronic circuit that converts a binary number into a continuously varying value.)

Digital Camera Memory Interface

Digital Filter for Sigma-Delta Modulator

External Interrupt

General-Purpose Input/Output (A realization of open ended transmission between devices on an embedded level. These pins available on a processor can be programmed to be used to either accept input or provide output to external devices depending on user desires and applications requirements.)

System Configuration

voltage reference buffer (STM32 specific)

Hash-based Message Authentication Code

Secure Hash Algorithm

Hardware Semaphore

Inter-Integrated Circuit (Bi-directional 2-wire bus standard for efficient inter-IC control.)

Inter-Processor Communication Controller

low-power timer (STM32 specific)

Reset and Clock Control

Random Number Generator

Serial Audio Interface (Mechanism used to transfer non-buffered audio data between processors and/or audio converters.)

Secure digital

System Management Bus

Serial Peripheral Interface

Pulse Width Modulation

Android Runtime (see <https://source.android.com/devices/tech/dalvik>)

High Speed External oscillator (STM32 clock source)

High Speed Internal oscillator (STM32 clock source) or High Speed Synchronous Serial Interface (MIPI<sup>®</sup> Alliance standard)

Multi Speed Internal oscillator (STM32 clock source)

Low Speed External oscillator (STM32 clock source)

Low Speed Internal oscillator (STM32 clock source)

Real Time Clock

Universal Synchronous/Asynchronous Receiver/Transmitter

Local Interconnect Network

Application programming interface



Flash memories combine high density and cost effectiveness of EPROMs with the electrical erasability of EEPROMs. For this reason, the Flash memory market is one of the most exciting areas of the semiconductor industry today and new applications requiring in system reprogramming, such as cellular telephones, automotive engine management systems, hard disk drives, PC BIOS software for Plug & Play, digital TV, set top boxes, fax and other modems, PC cards and multimedia CD-ROMs, offer the prospect of very high volume demand.

Universal Asynchronous Receiver/Transmitter

Microcontroller Unit (MCUs have internal flash memory and are intended to operate with a minimum amount of external support ICs. They commonly are a self-contained, system-on-chip (SoC) designs.)

Real Time Operating System

TeleTYpewriter

Operating System

Artificial Intelligence